



- SEE CATALOG PAGE FOR MORE INFO.
- CLIC BAS IS DESIGNED FOR CEILING OR WALL MOUNTING WHERE MINIMAL PROFILE IS REQUIRED OR DESIRED.
- APPLICATIONS INCLUDE GENERAL AREA LIGHTING, HALLWAYS, CLOSETS, STAIRWELLS, ETC.
- STANDARD WIRING CONFIGURATION USES 1/8" IP THREADED TUBE CENTERED ON LUMINAIRE. ROUND WHITE J-BOX CONCEALER PLATE INCLUDED.
- CAN ALSO BE WIRED FROM THE END WITH CORD OR CORD AND PLUG.

ORDERING/SPECIFICATION GUIDE--CLIC BAS

COMPLETE NUMBER = AAAABBCCDDEEFGHIJKLM

AAAA	BB	CC	DD	EE	F	G	H	I	J	K	L	M
<u>CLIC BAS</u>	<u>MOUNTING</u>	<u>LAMP TYPE</u>	<u># OF LAMPS</u>	<u>LAMP WATTAGE</u>	<u>LAMP COLOR</u>	<u>EXTRUSION COLOR</u>	<u>SHIELDING</u>	<u>ENDCAP TYPE</u>	<u>WIRING</u>	<u>DIMMING</u>	<u>EMERGENCY</u>	<u>OTHER</u>
1950=	01=Custom 74=Wood Screws 75=Toggle Bolts	02=T5	01=1 02=2 03=3 etc.	08=14 W 08=21 W 09=24 W 10=28 W 11=35 W 13=39 W 18=54 W	2=830 3=835 4=841 5=880 6=885 7=Red 8=Green 9=Blue	1=Clear Anodized 2=White 3=Custom	0=None 1=Acrylic Lens 3=Metal Louver	1=Custom Color 4=White Plastic 6=Gray Plastic	1=Portable w/ Plug 2=Hardwire w/ Cord 4=Hardwire w/ 1/8IP Tube (Includes Canopy Cover)	1=Non-Dimming 2=Dim 10% 120 V 3=Dim 1% 120 V 4=Dim 10% 277V 5=Dim 1% 277V 6=Custom Dim 120V 7=Custom Dim 277V 8=Dim 0-10V 120V 9=Dim 0-10V 277V	1=Non-Emergency 2=Emerg 120V 3=Emerg 277V	0=Standard