



- SEE CATALOG PAGE FOR MORE INFO.
- CLIC GEMINI IS DESIGNED FOR SURFACE MOUNTED AREA LIGHTING WHERE MINIMAL PROFILE IS REQUIRED OR DESIRED.
- STANDARD POWER FEED IS THROUGH CUBE WITH 1/8 IP THREADED TUBE.
- STANDARD MOUNTING INCLUDES TWO CANOPY COVERS WITH ALL NECESSARY HARDWARE.
- INTEGRAL UNIVERSAL BALLAST.

ORDERING/SPECIFICATION GUIDE--CLIC GEMINI

COMPLETE NUMBER = AAAABBCCDDEEFGHIJKLM

AAAA	BB	CC	DD	EE	F	G	H	I	J	K	L	M
<u>CLIC GEMINI</u>	<u>MOUNTING</u>	<u>LAMP TYPE</u>	<u># OF LAMPS</u>	<u>LAMP WATTAGE</u>	<u>LAMP COLOR</u>	<u>EXTRUSION COLOR</u>	<u>SHIELDING</u>	<u>ENDCAP TYPE</u>	<u>WIRING</u>	<u>DIMMING</u>	<u>EMERGENCY</u>	<u>OTHER</u>
1930=	01=Custom 77=Gray Cubes 78=White Cubes	02=T5	02=2 04=4 06=6 etc.	08=14 W 08=21 W 09=24 W 10=28 W 11=35 W 13=39 W 16=54 W	2=830 3=835 4=841 5=860 6=865 7=Red 8=Green 9=Blue	1=Clear Anodized 2=White 3=Custom	1=Acrylic Lens	1=Custom 4=White Opaque 6=Gray Plastic	1=Portable w/ Plug 3=Hardwire w/ 1/8 IP Nipple	1=Non-Dimming 2=Dim 10% 120V 3=Dim 1% 120V 4=Dim 10% 277V 5=Dim 1% 277V 6=Custom Dim 120V 7=Custom Dim 277V 8=Dim 0-10V 120V 9=Dim 0-10V 277V	1=Non-Emergency	0=Standard