



- SEE CATALOG PAGE FOR MORE INFORMATION.
- PENDEL OFFICE ARC IS DESIGNED FOR TASK OR AREA LIGHTING WITH MINIMAL PROFILE, WITH UPLIGHT TO ENHANCE THE SPACE.
- CAN BE CONFIGURED WITH LENS OR METAL LOUVER.
- STANDARD POWER FEED IS A 1/8 IP TUBE AND ADJUSTABLE SUSPENSION WIRES ARE FIVE FEET. INCLUDES ONE CANOPY COVER WITH ALL NECESSARY HARDWARE.
- REMOTE UNIVERSAL BALLAST COMES STANDARD ATTACHED AS SHOWN IN LEFT PICTURE (BB=00); IT CAN ALSO BE DETACHED FROM SUSPENSION (BB=01 TO 46) (POWER THEN FEEDS FROM END OF BALLAST BOX).

ORDERING/SPECIFICATION GUIDE--PENDEL ARC

COMPLETE NUMBER = AAAABBCCDDEEFGHIJKLM

AAAA	BB	CC	DD	EE	F	G	H	I	J	K	L	M
<u>PENDEL ARC</u>	<u>MOUNTING</u>	<u>LAMP # OF TYPE</u>	<u>LAMP LAMPS</u>	<u>LAMP WATTAGE</u>	<u>LAMP COLOR</u>	<u>EXTRUSION COLOR</u>	<u>SHIELDING</u>	<u>ENDCAP TYPE</u>	<u>WIRING</u>	<u>DIMMING</u>	<u>EMERGENCY</u>	<u>OTHER</u>
1510=	00=Standard 01=Custom 03=MT0002 09=MT0008 10=MT0009 11=MT0010 12=MT0011 13=MT0012 14=MT0013 28=MT0027 29=MT0028 30=MT0029 41=MT0040 43=MT0042 44=MT0043 46=MT0045	02=T5 01=1 02=2 03=3 etc.	08=14W 09=24W 10=28W 11=35W 13=39W 16=54W	2=830 3=835 4=841 5=860 6=865 7=Red 8=Green 9=Blue	1=Clear Anodized 2=White 3=Custom	0=None 1=Acrylic Lens 3=Metal Louver	1=Custom 2=Blue Translucent 3=White Translucent 4=White Opaque 5=Red Translucent 6=Gray Plastic 7=Gray Aluminum 8=White Aluminum	2=Hardwire w/ Cord 3=Hardwire w/ Conduit 4=Hardwire w/ 1/8IP Tube (Standard)	1=Non-Dimming 2=Dim 10% 120V 3=Dim 1% 120V 4=Dim 10% 277V 5=Dim 1% 277V 6=Custom Dim 120V 7=Custom Dim 277V 8=Dim 0-10V 120V 9=Dim 0-10V 277V	1=Non-Emergency 2=Emerg 120V 3=Emerg 277V	0=Standard 1=Ecosystem Type 1 2=Ecosystem Type 2 3=Ecosystem Type 3	