



- SEE CATALOG PAGE FOR MORE INFORMATION.
- REKTOR PENDANT CEILING LIGHT IS DESIGNED FOR DIRECT CEILING MOUNT AREA LIGHTING WITH MINIMAL PROFILE.
- CAN BE CONFIGURED WITH ACRYLIC LINEAR SPREAD LENS OR METAL LOUVER. BOTH ARE REMOVABLE FOR LAMP MAINTENANCE WITHOUT THE NEED TO REMOVE THE ENDCAPS.
- STANDARD POWER FEED PROVIDED BY 1/8 IP THREADED NIPPLE CENTERED IN FIXTURE. INCLUDES ONE CANOPY COVER WITH ALL NECESSARY HARDWARE.
- SECURED TO CEILING VIA TOGGLE BOLTS.

ORDERING/SPECIFICATION GUIDE--REKTOR CEILING

COMPLETE NUMBER = AAAABBCCDDEEFGHIJKLM

AAAA	BB	CC	DD	EE	F	G	H	I	J	K	L	M
<u>Rektor Ceiling</u>	<u>MOUNTING</u>	<u>LAMP TYPE</u>	<u># OF LAMPS</u>	<u>LAMP WATTAGE</u>	<u>LAMP COLOR</u>	<u>EXTRUSION COLOR</u>	<u>SHIELDING</u>	<u>ENDCAP TYPE</u>	<u>WIRING</u>	<u>DIMMING</u>	<u>EMERGENCY</u>	<u>OTHER</u>
2000=	75=Toggle Bolts	02=T5	01=1 02=2 03=3 etc.	08=14W 08=21W 09=24W 10=28W 11=35W 13=39W 18=54W	2=830 3=835 4=841 5=880 6=885 7=Red 8=Green 9=Blue	1=Clear Anodized 2=White 3=Custom	0=None 1=Acrylic Lens 3=Metal Louver	1=Custom 7=Gray Aluminum 8=White Aluminum	4=Hardwire w/ 1/8 IP	1=Non-Dimming 2=Dim 10% 120V 3=Dim 1% 120V 4=Dim 10% 277V 5=Dim 1% 277V 6=Custom Dim 120V 7=Custom Dim 277V 8=Dim 0-10V 120V 9=Dim 0-10V 277V	1=Non-Emergency	0=Standard