



- SEE CATALOG PAGE FOR MORE INFORMATION.
- REKTOR PENDANT DOWN LIGHT IS DESIGNED FOR SUSPENDED TASK OR AREA LIGHTING WITH MINIMAL PROFILE.
- CAN BE CONFIGURED WITH ACRYLIC LINEAR SPREAD LENS OR METAL LOUVER.
- STANDARD POWER CABLE AND ADJUSTABLE SUSPENSION WIRES ARE FIVE FEET. THE SUSPENSION WIRES SLIDE ALONG THE MOUNTING CHANNEL FOR A MORE FLEXIBLE INSTALLATION. INCLUDES ONE CANOPY COVER WITH ALL NECESSARY HARDWARE.
- CAN BE CONFIGURED WITH HO OR NORMAL LAMP COMBINATION.

ORDERING/SPECIFICATION GUIDE--REKTOR PENDANT DOWN LIGHT

COMPLETE NUMBER = AAAABBCCDDEEFGHIJKLM

| AAAA | BB | CC | DD | EE | F | G | H | I | J | K | L | M |
|---------------------|------------------------|-------------|------------------------------|--|---|---|--|---|--|---|---|--|
| REKTOR | | LAMP | # OF | LAMP | LAMP | EXTRUSION | | ENDCAP | | | | |
| <u>Down Pendant</u> | <u>MOUNTING</u> | <u>TYPE</u> | <u>LAMPS</u> | <u>WATTAGE</u> | <u>COLOR</u> | <u>COLOR</u> | <u>SHIELDING</u> | <u>TYPE</u> | <u>WIRING</u> | <u>DIMMING</u> | <u>EMERGENCY</u> | <u>OTHER</u> |
| 2005= | 01=Custom 85=RK0002 | 02=T5 | 01=1 02=2 03=3 etc. | 06=14W 08=21W 09=24W 10=28W 11=35W 13=39W 16=54W | 2=830 3=835 4=841 5=860 6=885 7=Red 8=Green 9=Blue | 1=Clear Anodized 2=White 3=Custom | 0=None 1=Acrylic Lens 3=Metal Louver | 1=Custom 7=Gray Aluminum 8=White Aluminum | 1=Portable w/ Plug 2=Hardwire w/ Cord | 1=Non-Dimming 2=Dim 10% 120V 3=Dim 1% 120V 4=Dim 10% 277V 5=Dim 1% 277V 6=Custom Dim 120V 7=Custom Dim 277V 8=Dim 0-10V 120V 9=Dim 0-10V 277V | 1=Non-Emergency 2=Emergency 120V 3=Emergency 277V | 0=Standard 1=Ecosystem Type 1 2=Ecosystem Type 2 3=Ecosystem Type 3 |