



- SEE CATALOG PAGE FOR MORE INFORMATION.
- REKTOR PENDANT UP/DOWN LIGHT IS DESIGNED FOR SUSPENDED TASK OR AREA LIGHTING WITH MINIMAL PROFILE.
- CAN BE CONFIGURED WITH ACRYLIC LINEAR SPREAD LENS OR METAL LOUVER. INCLUDES AS STANDARD A FROSTED ACRYLIC LENS COVERING THE UP LAMPS.
- STANDARD POWER CABLE AND ADJUSTABLE SUSPENSION WIRES ARE FIVE FEET. THE SUSPENSION WIRES SLIDE ALONG THE MOUNTING CHANNEL FOR A MORE FLEXIBLE INSTALLATION. INCLUDES ONE CANOPY COVER WITH ALL NECESSARY HARDWARE.
- CAN BE CONFIGURED WITH HO AND NORMAL LAMP COMBINATION.

ORDERING/SPECIFICATION GUIDE--REKTOR PENDANT UP and DOWN LIGHT

COMPLETE NUMBER = AAAABCCDDEEFGHIJKLM

AAAA	BB	CC	DD	EE	F	G	H	I	J	K	L	M
REKTOR		LAMP # OF	LAMP	LAMP	EXTRUSION		ENDCAP					
<u>Up/Dn Pendant</u>	<u>MOUNTING</u>	<u>TYPE</u>	<u>LAMPS</u>	<u>WATTAGE</u>	<u>COLOR</u>	<u>COLOR</u>	<u>SHIELDING</u>	<u>TYPE</u>	<u>WIRING</u>	<u>DIMMING</u>	<u>EMERGENCY</u>	<u>OTHER</u>
2015=	01=Custom 85=RK0002	02=T5	02=2 04=4 06=6 etc.	06=14W 08=21W 09=24W 10=28W 11=35W 13=39W 16=54W	2=830 3=835 4=841 5=860 6=865 7=Red 8=Green 9=Blue	1=Clear Anodized 2=White 3=Custom	0=None 1=Acrylic Lens 3=Metal Louver	1=Custom 7=Gray Aluminum 8=White Aluminum	1=Portable w/ Plug 2=Hardwire w/ Cord	1=Non-Dimming 2=Dim 10% 120V 3=Dim 1% 120V 4=Dim 10% 277V 5=Dim 1% 277V 6=Custom Dim 120V 7=Custom Dim 277V 8=Dim 0-10V 120V 9=Dim 0-10V 277V	1=Non-Emergency	0=Standard 1=Ecosystem Type 1 2=Ecosystem Type 2 3=Ecosystem Type 3