



- SEE CATALOG PAGE FOR MORE INFORMATION.
- WINDSOR IS DESIGNED FOR RECESSED AREA OR ACCENT LIGHTING WITH MINIMAL PROFILE.
- UTILIZES “TILT AND REMOVE” ACRYLIC FROSTED LENS FOR EASY LAMP MAINTENANCE.
- STANDARD POWER FEED INCLUDES 1/2” FLEXIBLE CONDUIT CONNECTOR ONLY; DUE TO THE NARROW OPENING, THE POWER FEED CONDUIT MUST BE INSTALLED FROM THE J-BOX PRIOR TO FINISHING THE CEILING!
- CAN ALSO BE CONFIGURED FOR 2 FOOT AND 4 FOOT GRID CEILING INSTALLATION.

ORDERING/SPECIFICATION GUIDE--WINDSOR

COMPLETE NUMBER = AAAABBCCDDEEFGHIJKLM

AAAA	BB	CC	DD	EE	F	G	H	I	J	K	L	M
<u>WINDSOR</u>	<u>MOUNTING</u>	<u>LAMP TYPE</u>	<u># OF LAMPS</u>	<u>LAMP WATTAGE</u>	<u>LAMP COLOR</u>	<u>EXTRUSION COLOR</u>	<u>SHIELDING</u>	<u>ENDCAP TYPE</u>	<u>WIRING</u>	<u>DIMMING</u>	<u>EMERGENCY</u>	<u>OTHER</u>
2200=	00=Standard 76=Grid Clips	02=T5	01=1 02=2 03=3 etc.	06=14W 08=21W 09=24W 10=28W 11=35W 13=39W 16=54W	2=830 3=835 4=841 5=860 6=865 7=Red 8=Green 9=Blue	1=Clear Anodized	0=None 2=Acrylic Frosted Lens	7=Gray Aluminum	3=Hardwire w/ Conduit	1=Non-Dimming 2=Dim 10% 120V 3=Dim 1% 120V 4=Dim 10% 277V 5=Dim 1% 277V 6=Custom Dim 120V 7=Custom Dim 277V 8=Dim 0-10V 120V 9=Dim 0-10V 277V	1=Non-Emergency 2=Emerg 120V 3=Emerg 277V	0=Standard 1=Ecosystem Type 1 2=Ecosystem Type 2 3=Ecosystem Type 3